



# INBOARD RACING COMMISSION FLATBOTTOM SAFETY INSPECTION -

Revised January, 2020

Boat Number \_\_\_\_\_ Class \_\_\_\_\_ Boat Name \_\_\_\_\_

Driver Helmet Type \_\_\_\_\_ Snell # \_\_\_\_\_ Color \_\_\_\_\_

Rider Helmet Type \_\_\_\_\_ Snell # \_\_\_\_\_ Color \_\_\_\_\_

Life Jacket: Category A A-100 B C ( ) Flotation Vest ( ) Sewn In Uniform

Rider Jacket: Category A A-100 B C ( ) Flotation Vest ( ) Sewn In Uniform

Sling Rating in Pounds/Leg \_\_\_\_\_ # Of Legs \_\_\_\_\_ Re Certification Date (Every 5 Years) \_\_\_\_\_

Driver Restraint Belts: Material: ( ) Nylon ( ) Poly Width \_\_\_\_\_

Release: ( ) Lever ( ) Rotary Condition \_\_\_\_\_

Flotation Required: Type \_\_\_\_\_ Location \_\_\_\_\_

Reinforced Cockpit Certification # \_\_\_\_\_ (Must be permanently mounted in boat) Yes No

Audio communication (radio, etc.) from shore to driver is mandatory. (Yes) (NO)

Air System: (YES) (NO) Comments \_\_\_\_\_

## Hull

( ) Steering – Cables & Pulleys ( ) Rudder and Bracket ( ) Strut

( ) Sling Attachment Lift Points – Accessible for viewing ( ) Motor Mounts ( ) Battery Mounts

( ) Propshaft Collars (2 screw or split) ( ) Fuel Lines ( ) Fuel Tank mounting/where \_\_\_\_\_

( ) Throttle Return Spring ( ) Drive Shaft Cover ( ) Whirlaway Functional

( ) Kill switch hooked to Jacket (Non Capsule only) Date tested \_\_\_\_\_

## Reinforced Cockpits

( ) Minimum 2" Clearance above driver to cockpit or canopy

( ) The top of the Front of the Cockpit will be a Max of 4" Below Eye Level

( ) Minimum 1/2" (9lb) Ethofoam Support behind Head ( ) Cockpit Area Sealed (Firewall)

( ) No Sharp Edges or Protrusions in Cockpit ( ) Energy Absorbing Foam Padding inside Cockpit

( ) Canopies Positive Air Flow ( ) Canopies Internal and External Release

( ) Mirror ( ) Fire Proof Drivers Suit (Restraint Boats Only)

## Trailer

Trailer # \_\_\_\_\_ ( ) Fire Extinguisher (Minimum 3A30BC) Date (5 Yr. Max) \_\_\_\_\_

INSPECTOR \_\_\_\_\_

EVENT \_\_\_\_\_

BOAT REP \_\_\_\_\_

DATE \_\_\_\_\_